

## ctools - Bug #1469

### Constructor of some cscripts breaks from python if no argument is given

06/01/2015 02:28 PM - Mayer Michael

<b>Status:</b>	Closed	<b>Start date:</b>	06/01/2015
<b>Priority:</b>	Immediate	<b>Due date:</b>	
<b>Assigned To:</b>	Mayer Michael	<b>% Done:</b>	100%
<b>Category:</b>		<b>Estimated time:</b>	0.00 hour
<b>Target version:</b>	1.0.0		
<b>Description</b>			
When running a cscript from within python, e.g.			
<pre>import csresmap resmap = csresmap.csresmap()</pre>			
The above code will throw an error due to the following line of code int the cscripts:			
<pre>if isinstance(argv[0],gammalib.GObservations):     self.obs = argv[0]     argv = argv[1:]</pre>			
It has to be assured that len(argv)>0 first! the following cscripts are affected:			
<ul style="list-style-type: none"><li>• csresmap</li><li>• csspec</li><li>• cslightcrv</li></ul>			

#### History

##### #1 - 06/01/2015 02:30 PM - Mayer Michael

- Status changed from New to Pull request
- % Done changed from 0 to 100

fix available on [1469-fix-cscript-python-constructor](#)

##### #2 - 06/01/2015 05:56 PM - Knödseder Jürgen

- Status changed from Pull request to Closed
- Target version set to 1.0.0

Merged into devel.